

Customer: _____

Contact: _____

Lead Time: _____

SO# _____



PRODUCTS INC.

judy@afwood.com
michelle@afwood.com

5665 Sterling Drive
Howell, Mi. 48843
Phone: 800-367-3293
Fax: 517-545-5633

Date: _____

PO# _____

Order Quote

Page: _____ of _____

Line	Quantity	Handing	Material	Frame Type	Opening Width	Opening Height	Jamb Depth	Throat	Profile	Head Face	Jamb Face	Rabbets	Fire Label (Min.)	Anchors	Locations	Hinges	Strike	Closer (RA or PA)	Construction	Glazing Bead	Loose/Installed	Mutes	See Notes	Mark #	Price
1																									
2																									
3																									
4																									
5																									
6																									

Material Legend	Frame Type Legend	Anchor Legend	Locations Legend	Strike Legend	Packaging
6C -16Ga CRS 6A -16 Ga A60 4C -14 Ga CRS 4A -14 Ga A60 2C -12 Ga CRS 2A -12 Ga A60	S - Single P - Pair C - Cased Open M - Communicating D - Double Egress E - Elevation (Dwg.) BL - Borrowed Lite	CO - Compression Anchors EM - Existing Masonry Anchors MP - Multi-purpose Anchors SS - Steel Stud Anchors TA - T-Anchors WA - Wire Anchors WS - Wood Stud Anchors NO - No Anchors NT - Provide Anch:	AM - Amweld BM - Benchmark HMF CE - Ceco CU - Curries FE - Fenestra ME - Mesker PI - Pioneer RE - Republic ST - Steelcraft * - See Chart	A - ASA B - Blank C - Conc. Vertical Rod D - Deadlock F - Flush Bolt R - Rim Panic S - Surface Vertical Rod T - T Strike AD - ASA X Deadlock TD - T Strike X Deadlock	Type: _____ Total: _____ Hinge Legend A - 4.5 S.W. D - 5 H.W. B - 4.5 H.W. N - None C - 5 S.W. E - Enter Below Construction Legend KD - Knock Down FW - Face Welded CW - Cont. Welded

Profiles:	Custom	Chart

Notes	Line
	1
	2
	3
	4
	5

QUOTES ARE VALID NO MORE THAN 30 DAYS FROM DATE OF ISSUE